

Material Safety Data Sheet

Infosafe No™ 1PJ10 Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : Dual Coat Satin

Classified as hazardous

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name Dual Coat Satin
Product Code DUCOSA
Company Name Peerless Jal Pty Ltd (ABN 53 006 489 345)
Address 10-12 Raglan Street Preston
VIC 3072
Telephone/Fax Number Tel: (03) 9416 6700
Fax: (03) 9416 8516
Recommended Use As a semi permanent finishing coat on internal timber, cork, parquetry and composite floors.

2. HAZARDS IDENTIFICATION

Hazard Classification Classified as hazardous
HAZARDOUS SUBSTANCE.
DANGEROUS GOODS.

Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC).
Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization Liquid

Ingredients	Name	CAS	Proportion	Hazard Symbol	Risk Phrase
	Oil based resins	N/A	10-60 %		
	Micro, macro and polyethylene waxes	N/A	5-10 %		
	Dryers	N/A	0-10 %		
	Mineral Turpentine	64742-82-1	20-30%		

4. FIRST AID MEASURES

Inhalation Remove to fresh air. If breathing stopped, give artificial respiration and seek urgent medical advice.
Ingestion If swallowed, do NOT induce vomiting. Give a glass of water. Do not give anything by mouth to an unconscious person. Seek medical advice.
Skin Remove contaminated clothing, wash affected area with soap & water.
Eye Hold eyelids open and flood with water for at least 15 minutes & see a Doctor.
Advice to Doctor Extreme care must be taken to prevent aspiration.
Tends to break into foam if the patient vomits. When vomiting occurs, hold patient with head below the hips to prevent pulmonary aspiration.
Aspiration into lungs may lead to chemical pneumonitis.

5. FIRE FIGHTING MEASURES

Specific Hazards Extinguish small fires with Foam, Dry Chemical or CO2.
Can readily form flammable mixtures at or above Flash Point (35°C).
Fire fighters must use self-contained breathing apparatus in confined or poorly ventilated spaces. Cool intact storage drums with water spray.
Hazchem Code 3[Y]

6. ACCIDENTAL RELEASE MEASURES

Spills & Disposal Eliminate all ignition sources. Remove leaking containers to detached area. Cover spill with absorbent material and pick up to sealable container for disposal to an approved hazardous waste facility.

7. HANDLING AND STORAGE

Conditions for Safe Storage Store in well-ventilated area. Store away from heat or ignition sources strong oxidizing agents.

Material Safety Data Sheet

Infosafe No™ 1PJ10 Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : Dual Coat Satin

Classified as hazardous

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards TWA 100ppm max-recommended (Turpentine substitute).

Engineering Controls Ventilation: Air circulation from open doors or windows is adequate, especially in high ceiling buildings such as gymnasiums and stadiums. In small enclosed poorly ventilated areas, mechanical explosion proof extraction ventilation, or an approved organic vapour respirator is recommended.

Personal Protective Equipment Avoid contact with skin and eyes. Splash proof goggles, coveralls and viton gloves are recommended when handling. In confined poorly ventilated areas an approved organic vapour respirator is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Liquid

Appearance Slightly Viscous Amber Liquid with a Paraffinic odour

Boiling Point Above 147°C

Solubility in Water Insoluble

Specific Gravity 0.915 ± 0.005

Vapour Pressure <1 (at 25°C)

Volatile Component Approximately 60.0%

Flash Point 35°C (closed cup)

Flammability Flammable Liquid.
Keep away from heat, sparks or naked flames.

Flammable Limits - Lower 0.9%

Flammable Limits - Upper 7.0%

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

Inhalation Concentrated vapour of solvent may cause headaches and dizziness, and in severe cases uncoordination.

Ingestion Harmful if swallowed. Causes nausea, vomiting, pulmonary irritation. Retention of larger volumes (>1ml/kg) may result in symptoms of CNS depression, irritation, weakness, dizziness, unconsciousness and convulsions.

Skin Slightly irritating to the skin. Prolonged or repeated contact may lead to dermatitis due to the defatting nature of the product.

Eye Mildly irritating to the eye.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

14. TRANSPORT INFORMATION

Transport Information Classified as dangerous goods according to the Transport of Dangerous Goods (ADG) Code.

U.N. Number 1866

Proper Shipping Name RESIN SOLUTION

DG Class 3

Hazchem Code 3[Y]

Special Precautions for User Correct Shipping Name: Resin Solution, Flammable (Contains: Mineral Turpentine)

Packaging Method 3.8.3RT1,RT7

Material Safety Data Sheet

infosafe
CS: 1.9.606

Page: 3 of 3

Infosafe No™ 1PJ10 Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : **Dual Coat Satin**

Classified as hazardous

Packing Group	III
EPG Number	3A1
IERG Number	14
UN Number (Road Transport)	1866
Other Information	This MSDS summarises our best knowledge of health and safety hazard information of the product and how to safely handle and use the product.

15. REGULATORY INFORMATION

Regulatory Information	Classified as hazardous HAZARDOUS SUBSTANCE. SCHEDULED POISON.
Poisons Schedule	Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC). Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). S5

16. OTHER INFORMATION

Technical Contact Point	Technical Department 10-12 Raglan Street Preston, VIC, 3072 Tel: (03)9416 6700 (BH) Fax: (03)9416 8516
Other Information	ID No.: DUCOSA ...End Of MSDS...

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.