

Material Safety Data Sheet

Infosafe No™ 1PJ2P Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : LAZER FLOOR STRIPPER

Classified as hazardous

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name LAZER FLOOR STRIPPER
Product Code ST25
Company Name Peerless Jal Pty Ltd (ABN 53 006 489 345)
Address 10-12 Raglan Street Preston
VIC 3072
Telephone/Fax Number Tel: (03) 9416 6700
Fax: (03) 9416 8516
Emergency Contact Address Technical Department
10-12 Raglan Street
Preston
VIC 3072
Tel: (03) 9416 6700
Fax: (03) 9416 8516
Recommended Use To remove aged or dirty water based seals, polishes and waxes from vinyl tiles and sheeting and linoleum.
Other Names Name Product Code
STRIP OFF

2. HAZARDS IDENTIFICATION

Hazard Classification Classified as hazardous
HAZARDOUS SUBSTANCE.
DANGEROUS GOODS.

Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC).
Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
Risk Phrase(s) Classified as hazardous
R36/37/38 Irritating to eyes, respiratory system and skin.
Safety Phrase(s) S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization Liquid
Ingredients

<u>Name</u>	<u>CAS</u>	<u>Proportion</u>	<u>Hazard Symbol</u>	<u>Risk Phrase</u>
Ethylene glycol butyl ether	111-76-2	0-10 %		
Industrial Ethanol	64-17-5	0-10 %		
Ethanolamine	141-43-5	0-10 %		
Perfume	N/A	0-10 %		
Water	N/A	To 100%		

4. FIRST AID MEASURES

Inhalation Remove to fresh air. Rinse mouth and nasal passage with water.
Ingestion Do NOT induce vomiting. Give a glass of water and contact a doctor or the Poisons Information Centre. Phone 13 11 26.
Skin Remove contaminated clothing, (launder before re-use) and wash affected area with soap & water.
Eye Hold eyelids open and flood with water for at least 15 minutes & see a Doctor.
Advice to Doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Specific Hazards Presents no known fire or explosive hazards and forms no known hazardous decomposition products.
Treat fire for materials actually involved in the fire.
Hazchem Code 2X

Material Safety Data Sheet

Infosafe No™ 1PJ2P Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : LAZER FLOOR STRIPPER

Classified as hazardous

6. ACCIDENTAL RELEASE MEASURES

Spills & Disposal Avoid secondary accidents, floors may become slippery. Pick up excess for disposal and rinse residue with water.

7. HANDLING AND STORAGE

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards LD50 470mg/Kg for Ethylene glycol butyl ether.
Ethylene glycol ether OSHA standard 50ppm & ACGIH 25ppm.
TLV for Ethanol 1000ppm.

Engineering Controls Ventilation: No special requirements.

Personal Protective Equipment Avoid contact with skin and eyes.
Wear impervious gloves while handling or pouring.
Wear goggles or safety glasses and protective footwear while pouring or diluting.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Liquid

Appearance Water white liquid of Glycol odour.

Boiling Point 105°C (@ 760mm Hg)

Solubility in Water Infinite.

Specific Gravity 0.999 ± 0.005

pH Value 11.5 - 12.5

Vapour Pressure Not determined.

Volatile Component 100%

Flash Point Non flammable.

Flammability Non flammable.

Flammable Limits - Lower Not applicable.

Flammable Limits - Upper Not applicable.

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

Inhalation Inhalation of concentrated vapour may cause nose, mouth and throat irritation.

Ingestion Can result in nausea, vomiting and stomach pain.

Skin Irritant due to defatting nature of the product. Repeated or prolonged contact may cause dermatitis.

Eye Slight pain, moderate irritation and possible corneal injury.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste Disposal Consign to chemical dump by licensed chemical waste hauler to be disposed of within local authority laws.

14. TRANSPORT INFORMATION

Transport Information Classified according to the Transport of Dangerous Goods (ADG) Code.

U.N. Number 1760

Proper Shipping Name CORROSIVE LIQUID, N.O.S.

Material Safety Data Sheet

infosafe
CS: 1.9.606

Page: 3 of 3

Infosafe No™ 1PJ2P Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : **LAZER FLOOR STRIPPER**

Classified as hazardous

DG Class	8
Hazchem Code	2X
Special Precautions for User	Correct Shipping Name: Corrosive Liquid N.O.S. (Contains: Amine)
Packing Group	II
EPG Number	8A1
IERG Number	37
UN Number (Road Transport)	1760
Other Information	This MSDS summarises our best knowledge of health and safety hazard information of the product and how to safely handle and use the product.

15. REGULATORY INFORMATION

Regulatory Information	Classified as hazardous HAZARDOUS SUBSTANCE. SCHEDULED POISON.
Poisons Schedule	Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC). Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). S5
Hazard Category	Irritant

16. OTHER INFORMATION

Technical Contact Point	Technical Department 10-12 Raglan Street Preston VIC 3072 Tel: (03) 9416 6700 (BH) Fax: (03) 9416 8516
Other Information	ID No.: ST25 ...End Of MSDS...

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.