

Material Safety Data Sheet

Infosafe No™ YSY4M Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : **SUPER FINISH SEAL**

Classified as hazardous

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Chemical Product and Company Identification Technical Department:
Tel: (03)9416 6700 (BH)
Fax: (03)9416 8516
Email: sales@peerlessjal.com.au
Web: www.peerlessjal.com.au

Product Name SUPER FINISH SEAL

Product Code SE04

Company Name Peerless Jal Pty Ltd (ABN 53 006 489 345)

Address 10-12 Raglan Street Preston
Victoria 3072 Australia

Telephone/Fax Number Tel: (03) 9416 6700
Fax: (03) 9416 8516

Email sales@peerlessjal.com

Recommended Use As a semi permanent-finishing coat on internal timber, cork, parquetry and composite floors.

Other Information The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising from or in any way connected with the handling, storage, use or disposal of the material.

2. HAZARDS IDENTIFICATION

Hazard Classification Classified as hazardous
HAZARDOUS SUBSTANCE.
NON-DANGEROUS GOODS.

Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC).
Not Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization Liquid

Ingredients	Name	CAS	Proportion	Hazard Symbol	Risk Phrase
	ALKYD RESIN	N/A	10-60 %		
	Dryers	N/A	0-10 %		
	White Spirits	8042-75-5	65%		

4. FIRST AID MEASURES

Inhalation Remove to fresh air. If breathing stopped, give artificial respiration and call a doctor.

Ingestion If swallowed, do NOT induce vomiting. Give a glass of water. If poisoning occurs, contact a Doctor or the Poisons Information Centre. Phone 13 11 26.

Skin Remove contaminated clothing, wash affected area with soap & water.

Eye Hold eyelids open and flood with water for at least 15 minutes & see a Doctor.

Advice to Doctor Treat symptomatically.
Consult Poisons Information Centre.

5. FIRE FIGHTING MEASURES

Specific Hazards Extinguish small fires with Foam, Dry Chemical or CO2.
Can readily form flammable mixtures at or above Flash Point (35°C).
Fire fighters must use self-contained breathing apparatus in confined or poorly ventilated spaces. Cool intact storage drums with water spray.

Hazchem Code 3[Y]

Material Safety Data Sheet

Infosafe No™ YSY4M Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : **SUPER FINISH SEAL**

Classified as hazardous

6. ACCIDENTAL RELEASE MEASURES

Spills & Disposal Eliminate all ignition sources. Remove leaking containers to detached area. Cover spill with absorbent material and pick up to sealable container for disposal to an approved hazardous waste facility.

7. HANDLING AND STORAGE

Conditions for Safe Storage Store in well-ventilated area. Store away from heat or ignition sources strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards TLV 100ppm max recommended (White Spirits).

Engineering Controls Ventilation: Air circulation from open doors or windows is adequate, especially in high Ceiling buildings such as gymnasiums and stadiums. In small-enclosed poorly ventilated areas, mechanical explosion proof extraction ventilation, or an approved organic vapour respirator is recommended.

Personal Protective Equipment Avoid contact with skin and eyes. Splash proof goggles, coveralls and viton gloves are recommended when handling. In confined poorly ventilated areas an approved organic vapour respirator is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Liquid

Appearance Slightly viscous tan liquid with mineral spirit odour

Boiling Point 147 - 199°C (@ 760mm Hg)

Solubility in Water Insoluble

Specific Gravity 0.895 ± 0.005

Vapour Pressure Not Applicable

Viscosity Ford Cup #4 @ 27°C 39 - 41 sec.

Volatile Component Approx. 65.0%

Flash Point 35°C (closed cup)

Flammability Flammable Liquid.
Keep away from heat, sparks or naked flames.

Flammable Limits - Lower 0.9% (for white spirits)

Flammable Limits - Upper 7.0% (for white spirits)

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

Inhalation Concentrated vapour of solvent may cause headaches and dizziness, and in severe cases uncoordination.

Ingestion Moderately toxic may cause gastric irritation. Ingestion can result in vomiting and depression.

Skin Slightly irritating due to defatting nature. Prolonged or repeated contact may lead to dermatitis

Eye A severe eye irritant.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

14. TRANSPORT INFORMATION

Transport Information Classified according to the Transport of Dangerous Goods (ADG) Code and the Standards for the Uniform Scheduling of Drugs and Poisons.

Material Safety Data Sheet

infosafe
CS: 1.9.606

Page: 3 of 3

Infosafe No™ YSY4M Issue Date : January 2015 ISSUED by PLESSJAL

Product Name : **SUPER FINISH SEAL**

Classified as hazardous

U.N. Number	1866
DG Class	3
Hazchem Code	3[Y]
Special Precautions for User	Correct Shipping Name: RESIN SOLUTION, Flammable (Contains: Turpentine Substitute)
Packing Group	III
IERG Number	14
UN Number (Road Transport)	1866
Other Information	This MSDS summarises our best knowledge of health and safety hazard information of the product and how to safely handle and use the product.

15. REGULATORY INFORMATION

Regulatory Information	Classified as hazardous HAZARDOUS SUBSTANCE. SCHEDULED POISON.
Poisons Schedule	Classified as Hazardous according to criteria of National Occupational Health & Safety Commission, Australia (NOHSC). Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). S5

16. OTHER INFORMATION

Technical Contact Point	Technical Department 10-12 Raglan Street Preston VIC 3072 Tel: (03)9416 6700 (BH) Fax: (03)9416 8516
Other Information	ID No.: SE04 ...End Of MSDS...

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.